

## TECHNICAL INFORMATION

### APPLICATION

The Ortek cold store door range is perfectly suiting all cold room application and offer superior insulation properties.



### Leaf Option

Single and double leaf with 100mm thickness. Insulated with rigid polyurethane has a density of 42~44 kg/m<sup>3</sup>.

### Surface Option

PVDF, Platisol and Inox.

### Application and Operation Temperature

For chiller applications, up to 0° Celsius.

### Frame Profiles

Door leaf frame, frame and counter frame are anodized aluminium. Distinctive design of thermal bridge blocker between frame and counter frame. Stainless steel option available upon request.

### Accessories

EPDM gasket, handle with lock & hinges composite material. Hinges equipped with stainless steel lever inside. Heater 220V/30W on frame profile and in gasket upon request.

### Optional Items

Vision panel, Panic Bar, Door Closer, Automatic Opening Mechanism, Aluminium or Oil Threshold.

### Colour Options

RAL 9002, 9005, 1018, 1015, 7016, 6018, 3000, 9003, 9006

## TECHNICAL INFORMATION

### APPLICATION

The Ortek cold store door range is perfectly suiting all cold room application and offer superior insulation properties.



### Leaf Option

Single and double leaf with 120mm thickness. Insulated with rigid polyurethane has a density of 42~44 kg/m<sup>3</sup>.

### Surface Option

PVDF, Plastisol and Inox.

### Application and Operation Temperature

For freezer applications, up to -24° Celsius.

### Frame Profiles

Door leaf frame, frame and counter frame are anodized aluminium. Distinctive design of thermal bridge blocker between frame and counter frame. Stainless steel option available upon request.

### Accessories

EPDM gasket, handle with lock & hinges composite material. Hinges equipped with stainless steel lever inside. Heater 220V/30W on frame profile and in gasket upon request.

### Optional Items

Vision panel, Panic Bar, Door Closer, Automatic Opening Mechanism, Aluminium or Oil Threshold.

## TECHNICAL INFORMATION

### APPLICATION

The European cold store door range is perfectly suiting all cold room application and offer superior insulation properties.



### Leaf Option

Single and double leaf with 140mm thickness. Insulated with rigid polyurethane has a density of 42~44 kg/m<sup>3</sup>.

### Surface Option

PVDF, Plastisol and Inox.

### Application and Operation Temperature

For deep freezer applications, up to -40° Celsius.

### Frame Profiles

Door leaf frame, frame and counter frame are anodized aluminium. Distinctive design of thermal bridge blocker between frame and counter frame. Stainless steel option available upon request.

### Accessories

EPDM gasket, handle with lock & hinges composite material. Hinges equipped with stainless steel lever inside. Heater 220V/30W on frame profile and in gasket upon request.

### Optional Items

Vision panel, Panic Bar, Door Closer, Automatic Opening Mechanism, Aluminium or Oil Threshold.